

Sinar

SNR-21 series


Dry Type

TERMINAL BLOCK

A. POLYMER



B. BAKELITE



SPECIFICATIONS

PHASE	: 1 Ø
FREQUENCY	: 50/60 Hz
PRIMARY VOLTAGE	: 200-220 V
SECONDARY VOLTAGE	: 100-110 V
CLASS OF INSULATION	: F
STANDARD	: JIS - C5310

Type	Capacity (VA)	Ampere (A)	Dimension (mm)						Weight (kg)
			L	W	H	Lp	Wp	φ A X B	
SNR30 - 21	30	0.30	88	82	98	58	60	4.5 X 10	1.2
SNR50 - 21	50	0.50	88	86	98	58	65	4.5 X 10	1.3
SNR75 - 21	75	0.75	88	91	98	58	75	4.5 X 10	1.8
SNR100 - 21	100	1.0	89	86	103	71	65	4.5 X 10	2.2
SNR150 - 21	150	1.5	89	92	103	71	70	4.5 X 10	2.5
SNR200 - 21	200	2.0	101	102	112	62	74	5.5 X 10	3.5
SNR300 - 21	300	3.0	117	115	122	81	76	7 X 14	4.8
SNR500 - 21	500	5.0	133	131	142	97	82	7 X 14	7.3
SNR750 - 21	750	7.5	152	135	156	113	94	7 X 14	9.6
SNR1K - 21	1K	10	159	152	163	110	101	7 X 14	10.3
SNR1.5K - 21	1.5K	15	177	165	182	120	118	8 X 16	14.9
SNR2K - 21	2K	20	177	190	190	120	145	8 X 16	20.0
SNR3K - 21	3K	30	177	215	190	120	172	8 X 16	24.7
SNR4K - 21	4K	40	230	230	291	180	165	10 X 25	42.0
SNR5K - 21	5K	50	230	257	291	180	190	10 X 25	48.0

