

Sinar

SNR-41 series


Dry Type

TERMINAL BLOCK

A. POLYMER



B. BAKELITE



SPECIFICATIONS

PHASE	: 1 Ø
FREQUENCY	: 50/60 Hz
PRIMARY VOLTAGE	: 400-440 V
SECONDARY VOLTAGE	: 100-110 V
CLASS OF INSULATION	: F
STANDARD	: JIS - C5310

Type	Capacity (VA)	Ampere (A)	Dimension (mm)						Weight (kg)
			L	W	H	Lp	Wp	φ A X B	
SNR30 - 41	30	0,30	88	82	98	58	60	4.5 X 10	1,2
SNR50 - 41	50	0,50	88	86	98	58	65	4.5 X 10	1,3
SNR75 - 41	75	0,75	88	91	98	58	75	4.5 X 10	1,8
SNR100 - 41	100	1,0	89	86	103	71	65	4.5 X 10	2,2
SNR150 - 41	150	1,5	89	92	103	71	70	4.5 X 10	2,5
SNR200 - 41	200	2,0	101	102	112	62	74	5.5 X 10	3,5
SNR300 - 41	300	3,0	117	115	122	81	76	7 X 14	4,8
SNR500 - 41	500	5,0	133	131	142	97	82	7 X 14	7,3
SNR750 - 41	750	7,5	152	135	156	113	94	7 X 14	9,6
SNR1K - 41	1K	10	159	152	163	110	101	7 X 14	10,3
SNR1.5K - 41	1.5K	15	177	165	182	120	118	8 X 16	14,9
SNR2K - 41	2K	20	177	190	190	120	145	8 X 16	20,0
SNR3K - 41	3K	30	177	215	190	120	172	8 X 16	24,7
SNR4K - 41	4K	40	230	230	291	180	165	10 X 25	42,0
SNR5K - 41	5K	50	230	257	291	180	190	10 X 25	48,0

